BLAZE[™] WET LOCATION LED TAPE LIGHT

Performance and value for everyday projects. Our most popular tape light, available in a wide range of color temperatures and outputs. Suitable for wet locations (IP65).



BLAZE[™] 200/300 Wet Location



FEATURES & BENEFITS

- Precision color rendering
- Suitable for applications that are prone to splashing, spraying, or rain
- Compatible with Diode LED tape light accessories including channels, drivers, and more

QUICK SPECS

Voltage	12VDC & 24VDC			
Width	10mm			
CRI	90+			
Warranty	7-Year Limited Warranty			
Dimming	Dimmable			
Environment	Outdoor / Wet Location (IP65)			
Certification	UL Listed 2108			

Visit the product page on the website for specification sheets, install guides, IES files, and photometric reports.

DI	_	VOL	TAGE	_	MODEL	LUN	IEN SERIES	_	сст		_	LENG	тн
DI	_	12V	(12VDC)	_	BLBSC	1	(100 Lumen Range)	_	27	(2700K)	_	W016	(16.4 ft.)
		24V	(24VDC)			2	(200 Lumen Range)		30	(3000K)		W100	(100 ft.)
						3	(300 Lumen Range)		50	(5000K)			

EXAMPLE: 24V BLAZE™ 100 LUMENS 5000K WET LOCATION 100 FT. SPOOL = DI-24V-BLBSC1-50-W100

	120	/DC	24VDC					
	100 LUMEN RANGE	200 LUMEN RANGE	100 LUMEN RANGE	200 LUMEN RANGE	300 LUMEN RANGE			
	BLBSC1-W	BLBSC2-W	BLBSC1-W	BLBSC2-W	BLBSC3-W			
	Max. Run: 27 ft.	Max. Run: 20 ft.	Max. Run: 55 ft.	Max. Run: 40 ft.	Max. Run: 22 ft.			
	Cut Points: 2 in.	Cut Points: 1 in.	Cut Points: 4 in.	Cut Points: 4 in.	Cut Points: 2 in.			
	Wattage: 1.46 W/ft.	Wattage: 2.93 W/ft.	Wattage: 1.46 W/ft.	Wattage: 2.93 W/ft.	Wattage: 4.5 W/ft.			
ССТ	Lumens / ft.							
2700K	107	206	106	209	331			
3000K	116	221	114	226	337			
5000K	116	227	114	224	329			