



Wet/dry location model shown



Dry location model shown

## OMNIDRIVE™ Electronic Dimmable Drivers

OMNIDRIVE Electronic Dimmable Drivers provide smooth, flicker-free dimming for LED lighting systems. The OMNIDRIVE Driver comes with a built-in filter that eliminates flickering from 100% down to 10%. The Electronic Dimmable Drivers are compatible with a wide range of TRIAC controls, including: magnetic low voltage (MLV), electronic low voltage (ELV), and incandescent/halogen dimmer switches, as well as 3/4/5-Way and On/Off switching.

### Features & Benefits

- **Form factor** - small and compact
- **Location** - indoor and outdoor models
- **Dimming** - smooth and flicker-free from 100%-10%
- **Control** - compatible with TRIAC forward-phase and reverse-phase dimmer switches

- **Smooth Dimming**

Built-in filter for flicker-free dimming

- **Versatile**

Compatible with TRIAC dimmer switches

- **Safe**

Overload, thermal, and short-circuit protection

- **Warranty**

3-year warranty



90-135V <b>AC</b>	12V <b>DC</b>	24V <b>DC</b>	IP40	IP67
Input	Output	Output	IP Rating	IP Rating

### OMNIDRIVE Electronic Dimmable Drivers - 12V

Item #	Input	Output	Wattage	Location
DI-TD-12V-10W	90-135V AC	12V DC	10W	dry
DI-TD-12V-20W	90-135V AC	12V DC	20W	dry
DI-TD-12V-30W	90-135V AC	12V DC	30W	dry
DI-TD-12V-45W	90-135V AC	12V DC	45W	dry
DI-TD-12V-60W	90-135V AC	12V DC	60W	wet/dry
DI-TD-12V-80W	90-135V AC	12V DC	80W	wet/dry

### OMNIDRIVE Electronic Dimmable Drivers - 24V

Item #	Input	Output	Wattage	Location
DI-TD-24V-10W	90-135V AC	24V DC	10W	dry
DI-TD-24V-20W	90-135V AC	24V DC	20W	dry
DI-TD-24V-30W	90-135V AC	24V DC	30W	dry
DI-TD-24V-45W	90-135V AC	24V DC	45W	dry
DI-TD-24V-60W	90-135V AC	24V DC	60W	wet/dry
DI-TD-24V-80W	90-135V AC	24V DC	80W	wet/dry

### Compatible Dimmer Switches

Description	Item #
120V AC MLV, ELV, and incandescent dimmers	see compatibility list

Always refer to the website for the most current specifications and technical documents.