

SABER™

LED UNDER CABINET LIGHT

SABER™ makes installation simple for soft, diffused under cabinet and task lighting. These 120V direct-wire LED fixtures feature five field-selectable color temperatures (CCTs) to please every customer. Using the included accessories, connect fixtures together for long runs.

SABER™ fixtures are compatible with most popular TRIAC and ELV dimmers and dim smoothly to as low as 5%. SABER™ makes it cost-effective and easy to equip any space with professional-level LED task lighting.

FEATURES & BENEFITS

- Link multiple fixtures for long runs
- Diffused lighting with no hot spots
- TRIAC and ELV dimming down to 5%
- Concealed self-contained mounting

QUICK SPECS

Voltage	120VAC
CRI	90+
Warranty	5-Year Limited Warranty
Dimming	TRIAC and ELV dimming
Environment	Indoor / Damp Location (IP20)
Certification	ETL Certified

120
VAC

90+
CRI

TITLE
24

Visit the product page on the website for specification sheets, install guides, IES files, and photometric reports.



SPECIFICATIONS & SKU BUILDER

DI	VOLTAGE	MODEL	LENGTH	SABER CCT NOTE	ALL CCTs*
DI	120V (120VAC)	SABER	08 (8 in.) 14 (14 in.) 22 (22 in.) 33 (33 in.)	*CCTs are field selectable. Each SABER™ has the ability to utilize all CCT options.	27 (2700K) 30 (3000K) 35 (3500K) 40 (4000K) 50 (5000K)

EXAMPLE: 120V SABER™ 8 FT. SPOOL = DI-120V-SABER-08

120VAC				
	SABER-08	SABER-14	SABER-22	SABER-33
	Length: 8 in. Wattage: 5 W/fixture	Length: 14 in. Wattage: 9 W/fixture	Length: 22 in. Wattage: 11 W/fixture	Length: 33 in. Wattage: 16 W/fixture
CCT	Lumens	Lumens	Lumens	Lumens
2700K	256	498	624	876
3000K	265	516	637	890
3500K	270	516	628	867
4000K	279	541	667	942
5000K	280	547	672	954

Visit DiodeLED.com for additional connectors and accessories for SABER™.

