

SPOTMOD® 2 RECESSED GIMBAL LED FIXTURE

Add bright, focused light to any home or business. This compact and dimmable indoor/outdoor LED fixture integrates seamlessly into cabinetry, patios, shelving, and more. SPOTMOD® 2 is available in a 32° beam angle for a broader flood light and has a wet location DC plug for safe and secure installation in dry or wet locations.



FEATURES & BENEFITS

- Sleek, compact, and sturdy aluminum housing
- 32° beam angle
- Suitable for indoor and outdoor applications

QUICK SPECS

Voltage	12VDC
CRI	90+
Warranty	5-Year Limited Warranty
Dimming	Dimmable
Environment	Outdoor / Wet Location (IP65)
Certification	ETL Listed
Connector	Wet Location Plug (9mm)

Visit the product page on the website for specification sheets, install guides, IES files, and photometric reports.

DI	VOLTAGE	MODEL	TYPE	CCT	BEAM ANGLE	BA
DI	12V (12VDC)	SPOT	RG2	30 (3000K)	32 (32 degrees)	BA

EXAMPLE: 12V SPOTMOD® 2 RECESSED GIMBAL 3000K 32-DEGREE BEAM ANGLE = DI-12V-SPOT-RG2-30-32-BA

12VDC	
12V-SPOT-RG2	
Wattage: 2.1 W/fixture	
CCT	Lumens
3000K	174