


STREAMLITE™ WET LOCATION DIFFUSED LINEAR LIGHT

Dot-free linear lighting without any visible LEDs. Ideal for tight spaces and simple, impactful installations. Suitable for wet locations (IP65). 7-Year Limited Warranty.



24 VDC	90+ CRI	TITLE 24	 IP65
------------------	-------------------	---------------------------	---

FEATURES & BENEFITS

- Uniform, diffused light appears dotless even without a diffusing lens
- Very small size, ideal for tight spaces
- 180° beam angle for even light distribution
- Compatible with channels and other popular accessories

QUICK SPECS

Voltage	24VDC
Width	10mm
CRI	90+
Warranty	7-Year Limited Warranty
Dimming	Dimmable
Environment	Outdoor / Wet Location (IP65)
Certification	UL Listed 2108

Visit the product page on the website for specification sheets, install guides, IES files, and photometric reports.

DI	VOLTAGE	MODEL	CCT	LENGTH
DI	24V (24VDC)	STMLT	27 (2700K) 40 (4000K)	W016 (16.4 ft.)
		STMLT4	30 (3000K) GN (Green)	
			35 (3500K) RD (Red)	

EXAMPLE: 24V STREAMLITE™ 2700K 16.4 FT. SPOOL = DI-24V-STMLT-27-W016

24VDC		
	STMLT-W	STMLT4-W
	Max. Run: 20 ft. Cut Points: 1.8 in. Wattage: 3.3 W/ft.	Max. Run: 16.4 ft. Cut Points: 1.8 in. Wattage: 5.0 W/ft.
CCT	Lumens / ft.	Lumens / ft.
2700K	221	376
3000K	256	378
3500K	275	400
4000K	271	440
Green	285	—
Red	38	—