


VALENT® HIGH DENSITY LED TAPE LIGHT

Versatile, high density tape light for most applications. Full diffusion and dotless light when paired with channels.



24 VDC
90+ CRI
TITLE 24

FEATURES & BENEFITS

- Dense LED placement for uninterrupted linear light
- Precision color rendering
- Channel (extrusion) not required for heat sink

QUICK SPECS

Voltage	24VDC
Width	12mm
CRI	90+
Warranty	7-Year Limited Warranty
Dimming	Dimmable
Environment	Indoor / Damp Location (IP20)
Certification	UL Listed 2108
Connector	12mm Terminal Block

Visit the product page on the website for specification sheets, install guides, IES files, and photometric reports.

DI	VOLTAGE	MODEL	LUMEN SERIES	CCT	LENGTH
DI	24V (24VDC)	VL	2 (200 Lumen Range)	27 (2700K)	016 (16.4 ft.)
			3 (300 Lumen Range)	30 (3000K)	100 (100 ft.)
			5 (500 Lumen Range)	35 (3500K)	
				40 (4000K)	

EXAMPLE: 24V VALENT® 200 LUMENS 2700K 16.4 FT. SPOOL = DI-24V-VL2-27-016

24VDC

200 LUMEN RANGE

VL2

Max. Run: 55 ft.
Cut Points: 1.32 in.
Wattage: 1.72 W/ft.

300 LUMEN RANGE

VL3

Max. Run: 42 ft.
Cut Points: 1.32 in.
Wattage: 2.55 W/ft.

500 LUMEN RANGE

VL5

Max. Run: 29 ft.
Cut Points: 1.32 in.
Wattage: 4.28 W/ft.

CCT	Lumens / ft.	Lumens / ft.	Lumens / ft.
2700K	221	325	539
3000K	222	329	504
3500K	206	298	506
4000K	209	313	512