VALENT® WARM DIM HIGH DENSITY LED TAPE LIGHT

High density tape light that glows warmer as it dims. Convincingly replicate the warm, familiar glow of incandescent light with the simplicity of a two-wire LED tape light installation.





FEATURES & BENEFITS

- 3000-2000K, 2700-1800K, and 3000-1800K dimming ranges
- 150+ and 400+ lumens per foot
- Compatible with 12mm Terminal Block Connectors

QUICK SPECS

Voltage 24VDC Width 12mm CRI 90+

Warranty 7-Year Limited Warranty

Dimming Dimmable

Environment Indoor / Damp Location (IP20)

Certification UL Listed 2108

Connector 12mm Terminal Block

Visit the product page on the website for specification sheets, install guides, IES files, and photometric reports.

DI —	VOLTAGE	- I	MODEL –	CCT		_	LENG	TH	
DI —	24V (24VDC)	- \	VL1 —	WD2718	(2700K-1800K)	_	016	(16.4 ft.)	
		\	VL4	WD3020	(3000K-2000K)		100	(100 ft.)	
				WD3018	(3000K-1800K)				

EXAMPLE: 24V VALENT® WARM DIM 100 LUMENS 2700K-1800K 16.4 FT. SPOOL = **DI-24V-VL1-WD2718-016**

		24VDC							
		VL1-WD2718	VL1-WD3020	VL1-WD3018	VL4-WD2718	VL4-WD3020	VL4-WD3018		
		Max. Run: 62 ft. Cut Points: 3.28 in. Wattage: 1.54 W/ft.	Max. Run: 62 ft. Cut Points: 3.28 in. Wattage: 1.54 W/ft.	Max. Run: 62 ft. Cut Points: 3.28 in. Wattage: 1.54 W/ft.	Max. Run: 21 ft. Cut Points: 3.28 in. Wattage: 4.4 W/ft.	Max. Run: 21 ft. Cut Points: 3.28 in. Wattage: 4.4 W/ft.	Max. Run: 21 ft. Cut Points: 3.28 in. Wattage: 4.4 W/ft.		
CC.	Т	Lumens / ft.	Lumens / ft.	Lumens / ft.	Lumens / ft.	Lumens / ft.	Lumens / ft.		
2700K -	- 1800K	149 6	_	_	395 14	_	_		
3000K -	- 2000K	_	155 7	_	_	400 17	_		
3000K -	- 1800K	_	_	155 6	_	_	400 14		

LED DRIVERS	CONTROL SYSTEMS			
OMNIDRIVE® X See page 82 SWITCHEX® See page 86	Available Products Begin on page 76			