



Now Available for Pre-Order

24V Tape Light Upgrade For FLUID VIEW® & BLAZE™

NOW OFFERING THE BEST COLOR RENDERING & LONGEST MAX RUN LENGTHS IN THE INDUSTRY!

We've re-engineered our two best-selling tape light, FLUID VIEW® and BLAZE™, to improve the features that made them so popular over the years. The new FLUID VIEW® and BLAZE™ 24V Tape Light expands the traditional maximum run lengths over 12V platforms, perfect for larger projects and applications where long runs of tape light is crucial. Available in a wide range of color temperatures with 90+ CRI and high R values, the new FLUID VIEW® and BLAZE™ 24V Tape Light will make it easy to choose the perfect light for any application..

BENEFITS

- High 90+ CRI and R Values for true, vibrant colors
- Wide selection of CCT options for the perfect light
- Multiple UL Listings and Certifications
- Longer max run lengths decreases the number of components, saving time and money
- More lighting while complying to Class 2 Safety

FLUID VIEW & BLAZE TAPE LIGHT ADVANCEMENTS

Better color rendering brings out vibrant and a truer color spectrum for the best lighting experience.

Longer run lengths decreases the number of components, including drivers and connectors with faster installation times.

Class 2 requirements met on all maximum run lengths for electrical and fire safety.

Choose the perfect light for any application with multiple color temperatures to choose from.

America's largest provider of low-voltage linear LED tape light, Elemental LED offers industry leading warranties and best-in-class customer service.

12VDC tape light best performs **up to 16.4 ft.** on a single power source and is best for **smaller projects.**

24VDC tape light allows for **up to 67 ft.** on a single power source while still remaining **Class 2 compliant.** This is what makes 24V tape light the perfect choice for **large-scale** and **commercial projects.**

FLUID VIEW® Quick Specifications

Voltage	24VDC
CRI	90+ (12VDC: 80+)
Max. Linear Run	67 ft. (12VDC: 16.4 ft.)
Cuttable	Every 4 in. (12VDC: 2 in.)
CCT Options	2000K, 2400K, 2700K 2850K, 3000K, 3300K, 3500K, 3800K, 4200K, 4400K, 5000K, 6300K
Certifications	UL Listed, Class 2, RoHS

BLAZE™ Quick Specifications

Voltage	24VDC
CRI	90+ (12VDC: 80+)
Max. Linear Run	33 ft. (12VDC: 16.4 ft.)
Cuttable	Every 2 in. (12VDC: 1 in.)
CCT Options	2400K, 2700K 2850K, 3000K, 3300K, 3500K, 3800K, 4200K, 4400K, 5000K, 6300K
Certifications	UL Listed, Class 2, RoHS

Product specs subject to change. Visit the website for current technical/warranty specifications.

For orders and questions call **877.817.6028** or visit **www.DiodeLED.com** for product information.

