SPOTMOD[®] TILE & LINK LED Fixtures

We proudly introduce the next additions to the SPOTMOD® family: SPOTMOD TILE and SPOTMOD LINK. Both fixtures feature exceptional color rendering with 90+ CRI values and architectural grade styling with slim, ultra-sleek profiles. The single LED "Chip-on-Board" design provides a single light source shadow that is ideal for modern and sophisticated applications. Each lightweight fixture delivers 220+ lumens of light making them ideal for under cabinet and display lighting applications.

SPOTMOD[®] TILE

This ultra-bright and low-profile fixture can be easily surface mounted onto most surfaces with only two enclosed screws.

SPOTMOD[®] LINK

The SPOTMOD LINK features daisy chain connectors for multi-fixture installations (up to seven) and can be surface mounted or recess mounted.






SPOTMOD TILE			FINI	SHES	
CCT	LUMENS	WHITE	ALUMINUM	BLACK	BRONZE
2700К	220	DI-12V-SPOT-TL27-90-WH	DI-12V-SPOT-TL27-90-AL	DI-12V-SPOT-TL27-90-BL	DI-12V-SPOT-TL27-90-BR
3000К	220	DI-12V-SPOT-TL30-90-WH	DI-12V-SPOT-TL30-90-AL	DI-12V-SPOT-TL30-90-BL	DI-12V-SPOT-TL30-90-BR
4000K	220	DI-12V-SPOT-TL40-90-WH	DI-12V-SPOT-TL40-90-AL	DI-12V-SPOT-TL40-90-BL	DI-12V-SPOT-TL40-90-BR

For orders and questions call 877.817.6028 or visit www.DiodeLED.com for product information.







SPOTMOD[®] LINK & TILE Accessories

FEATURES & BENEFITS

- 90+ CRI: High R9-R14 values
- High lumen output
- Modern and resilient aluminum designs
- Easy to install

QUICK SPECS


Voltage	12VDC	
CRI	90+	
Power Consumption	3.6W	
Certification	UL Listed 2108	

Visit the product page on the website for specification sheets, install guides, and photometric reports.









SPOTMOD TILE 1ft. 2-pin (female) to DC (female) Adapter Cable SKU: DI-SPOT-TL-ADP Dimensions: 12 x 0.45 in. (L x Dia) Color: White

SPOTMOD TILE Power Distribution Splitter Box, 6-way SKU: DI-SPOT-TLSP6 Dimensions: 3 x 1 x 0.5 in. (L x W x H) Color: White

SPOTMOD TILE and LINK 5 ft 2-pin male to female Extension Cable SKU: DI-SPOT-5EXT

Dimensions: $60 \times .25 \times .25$ in. (L x W x H) Color: White

	\sim		FINISHES				
CCT	LUMENS	WHITE	ALUMINUM	BLACK	BRONZE		
2700К	240	DI-12V-SPOT-LK27-90-WH	DI-12V-SPOT-LK27-90-AL	DI-12V-SPOT-LK27-90-BL	DI-12V-SPOT-LK27-90-BR		
3000К	240	DI-12V-SPOT-LK30-90-WH	DI-12V-SPOT-LK30-90-AL	DI-12V-SPOT-LK30-90-BL	DI-12V-SPOT-LK30-90-BR		
4000K	240	DI-12V-SPOT-LK40-90-WH	DI-12V-SPOT-LK40-90-AL	DI-12V-SPOT-LK40-90-BL	DI-12V-SPOT-LK40-90-BR		

For orders and questions call 877.817.6028 or visit www.DiodeLED.com for product information.

