

WET LOCATION CONNECTORS (10.5mm)

SPECIFICATION SHEET

The following wet location connectors may be utilized in wet location environments. Never submerge these accessories under water. Connectors, extensions cables, etc. are not rated for in-wall installations. Wet Location Connectors have a Class 2 amp rating: 60W/5A @ 12VDC; 100W/4.17A @ 24VDC.

These Wet Location Accessories feature 10.5mm plugs. These plugs are compatible with the following UL-Listed Wet Location LED Strip Light options:

UL-Listed Wet Location FLUID VIEW® 12V LED Strip Light

UL-Listed Wet Location BLAZE™ 12V LED Strip Light

SPECIFICATIONS

Voltage: 300VAC Wire Type: AWM 758 UL 2464 copper stranded

20/2 AWG

Wire Diameter: 0.22 in. (5.5mm)

Jacket: Extruded PVC

Flammability: VW-1, FT2 Max Temperature: 176°F (80°C) Dimensions: See chart below

Certifications: UL R/C E339137 and/or E301305

Item #	Туре	Description	Image
DI-10MM-WL-DC-M-** DI-10MM-WL-DC-F-**	Wet Location Plug (10.5mm) to DC Adapter Connector	Attaches a wet location 10.5mm plug to a male DC accessory or plug-in adapter (not rated for wet location environments). Gender specification applies to the wet location connection only. • Dimensions: 7.5 x 0.45 in. (L x Dia)	
DI-10MM-WL-SCP-**	Wet Location Solder Connector Pairs (10.5mm Plugs)	Converts a wet location 10.5mm plug to a hard-wired connection (1 male & 1 female wet location plug). • Dimensions: 4.75 x 0.41 in. (L x Dia)	
DI-10MM-WLSP2-** DI-10MM-WLSP3-** DI-10MM-WLSP5-**	Wet Location Splitter Plug (10.5mm Plugs)	Splits a connection for wet location connectors. • Dimensions: 9.25 x 0.8 x 0.63 in. (L x W x H)	
DI-10MM-WL6EXT-** DI-10MM-WL12EXT-** DI-10MM-WL24EXT-**	Wet Location Extension Cable (10.5mm Plugs)	Creates an extension between wet location 10.5mm plugs. Male to female extension. • Dimensions: 6 x 0.41 in. (L x Dia) • Dimensions: 12 x 0.41 in. (L x Dia) • Dimensions: 24 x 0.41 in. (L x Dia)	

^{**} Products available in 25 pack bulk quantities. Add -25 to each item # for bulk quantities.



Toll Free: 877.817.6028 | Fax: 415.592.1596 | www.DiodeLED.com | info@DiodeLED.com | o 2017 Elemental LED, Inc. All rights reserved. Specifications are subject to change without notice.