

STREAMLITE™ Color 24V Diffused Linear Light

Dot-free linear lighting without any visible LEDs. Ideal for tight spaces and simple, impactful installations. Suitable for wet locations (IP65).

Date _____

Project Notes _____

FEATURES

- Uniform, diffused light appears dotless even without a diffusing lens
- Very small size, ideal for tight spaces
- 180° beam angle for even light distribution
- Compatible with Terminal Block Connectors, channels, and other popular accessory
- Suitable for wet locations (IP65)



ORDERING CODES

Order spools, and components for field assembly

OPTIONAL ORDERING CODES

Mounting, drivers, and assembly preference

Diode LED	Voltage	Model	CCT	Length	Channels	Finish	Mounting	Driver	Delivery				
DI													
	24V	STMLT STMLT4	GN (Green) RD (Red)	016 (16.4) ft.	SL (Slim) CA (Canal) S1 (S1) RC10 (10mm Round) SQ10 (10mm Square)	SQ (Square) 45 (45°) 45DCO (45° Deco) 90 (90° Sideview) ROD (Rod)	MI1 (1-inch Mud-In) REC (Recessed) SLR (Slim Recessed) GZR (Grazer) WF (Waveform)	AL (Aluminum) WH (White) BL (Black)	3M (3M Adhesive) MC (Mounting Clip) UC (U-Clip)	VC (Vertical Clip) HNG (Hanging Hardware) RC (Rotating Clip)	ELV (Electronic) O10 (0-10V) MAG (Magnetic) SWX (Switchex)	O/O (On / Off) LUT (Lutron) PoE (Power over Ethernet)	FIELD HYBRID FACTORY *See Delivery Options

Model	24V-STMLT
Voltage	24V
Wattage	3.3 W/ft.
Lumens Green	236/ft.
Red	42/ft.
Cut Points	2.5 in.
Max Run (ft.)	16.4 ft.
Max Run (Class 2)	29 ft.
LED Chips	176/ft.
CRI	95+
Dimensions	0.31 in. x 0.13 in. (W x H)
Environment	Indoor / Damp Location (IP20)
Ambient Temperature	-4 ~ 122°F (-20 ~ 50°C)
Operating Temperature	-4 ~ 176°F (-20 ~ 80°C)
Certification	UL Listed 2108
Warranty	7 Year

STREAMLITE™ Color 24V
Diffused Linear Light

Dot-free linear lighting without any visible LEDs. Ideal for tight spaces and simple, impactful installations. Suitable for wet locations (IP65).


Date _____

Project Notes _____


MECHANICAL DIAGRAMS

24V-STMLT

24V-STMLT4



CONNECTIONS



36 in. Bare Lead 20/2 AWG UL 2464 Wire with Strain Relief

36 in. Bare Lead 20/2 AWG UL 2464 Wire with Strain Relief

STREAMLITE™ Color 24V Diffused Linear Light

Dot-free linear lighting without any visible LEDs. Ideal for tight spaces and simple, impactful installations. Suitable for wet locations (IP65).


Date _____

Project Notes _____

ACCESSORIES


DI-STMLT-CKT-TTT (Tape-to-Tape)

Streamlite Tape-to-Tape Connector




DI-STMLT-CKT-SPL24 (Splice Connector)

Streamlite Splice Connector




DI-STMLT-CKT12-EXT (12 inch Extension)

Streamlite 12 inch Extension




DI-TB8-6JPR (6 in.) DI-TB8-60JPR (60 in.)

Jumper Cable (Tape-to-Tape)




DI-TB8-60SPL (60 in.) (Tape-to-Wire)

Splice Wire (Tape-to-Wire)




DI-TB8-90-TTT (Tape-to-Tape)

8mm 90° Tape-to-Tape Connector




DI-TB8-CONN-TTT (Tape-to-Tape)

8mm Tape-to-Tape Connector



DI-TB8-CONN-TTW (Tape-to-Wire)

8mm Tape-to-Wire Connector



DELIVERY OPTIONS

- **Field Assembly**

Stock items for in-field assembly. Fastest order fulfillment.

- **Factory + Field (Hybrid)**

Finished lengths of light with leads. Channels either bulk or factory finished. Some field assembly required.

- **Factory Assembly**

Fastest installation: fixtures fully assembled in the factory.

- Lumen value measured in accordance to IES LM-80-08. LED chips have a luminous flux range with a tolerance of +/- 5%.
- Each maximum run requires a dedicated power feed from the driver. Do not extend beyond the recommended maximum run length. Max run may exceed Class 2 limit. Actual wattage may differ from calculated wattage due to voltage drop across run.
- Do not install product in an environment outside the listed ambient temperature. Exceeding the maximum ambient temperature may damage LED chips, reduce the total lamp life, lumen output, and/or adversely impact color consistency.
- Actual efficacy value is dependent to specified LED driver (power supply). An estimated efficacy value can be calculated as follows: Lumen value divided by average power consumption per foot.
- Operating temperature is measured according to the minimum and maximum ambient temperature environment.

STREAMLITE™ Color 24V Diffused Linear Light

Dot-free linear lighting without any visible LEDs. Ideal for tight spaces and simple, impactful installations. Suitable for wet locations (IP65).

Date _____

Project Notes _____

CERTIFICATIONS

Safety

- UL Listed 2108 Flexible Lighting Systems. Certified for United States and Canada. File # E469769.

Performance

- Photometric & Colorimetry data measured in accordance to IES LM-79-08, in Elemental LED's Innovation Lab.

Safety / Warnings / Disclosures

1. Install in accordance with national and local electrical code regulations.
2. This product is intended to be installed and serviced by a qualified, licensed electrician.
3. Only use copper wiring. Use wires rated for at least 176°F (80°C) and certified for use with external connection of electrical equipment.
4. Each maximum run requires a dedicated power feed from the driver. Do not extend beyond the recommended maximum run length.
5. Tape light, attached wire leads, and additional extension cables, connectors, etc., are not rated for in-wall installation unless otherwise noted. Tape light and attached wire leads are field-cuttable.
6. Ensure applicable wire is installed between driver, fixture, and any controls in-between. When choosing wire, factor in voltage drop, amperage rating, and type (in-wall rated, wet location rated, etc.). Inadequate wire installation could overheat wires, and cause fire.
7. Do not install in environment where LED chips are exposed to direct sunlight as damage to the phosphor will occur.
8. Do not install in environment where excessive heat may exist (ex. close proximity to fireplace, etc.) See Ambient Temperature ratings
9. Do not install indoor LED tape light products in outdoor / wet location environments. Only wet location tape light models are rated for outdoor / wet locations.
10. Do not modify product beyond instructions or warranty will be void.
11. Tape light must be handled with care. Excessive handling, bending, and pressure may damage the product, voiding the warranty.
12. Actual color may vary from what is pictured on this sheet and other print materials due to the limitations of photographic processes.
13. We reserve the right to modify and improve the design of our fixtures without prior notice. We cannot guarantee to match existing installed fixtures for subsequent orders or replacements in regards to product appearance, CCT, or lumen output.

WARRANTY

Limited Warranty

- 7 Years

This warranty does not include the additional accessories referenced in this specification sheet. Complete warranty details for fixtures and additional accessories are available at www.diodeled.com/limited-warranty/ within the Policies section. For warranty related questions please contact product support.

Consumer's Acknowledgment

Elemental LED, Inc. stands behind its products when they are used properly and according to our specifications. By purchasing our products, the purchaser agrees and acknowledges that lighting design, configuration and installation is a complex process, wherein seemingly minor factors or changes in layout and infield adjustments can have a significant impact on an entire system. Choosing the correct components is essential. Elemental LED is able to work with the original purchaser to make an appropriate product selection to the extent of the limited information that the customer can provide, but it is virtually impossible for Elemental LED to design a system that foresees every unknown factor. For this reason, this Warranty does not cover problems caused by improper design, configuration or installation issues. Any statement from a Elemental LED employee or agent regarding a customer's bill of goods and/or purchase order is NOT an acknowledgment that the products purchased are designed and configured correctly. The purchase agrees and acknowledges that it is the customer's responsibility to adhere strictly to all information contained in the Product Specification Sheets.

There is often more than one way to design, configure and layout an LED lighting application properly to achieve the same lighting effect. Elemental LED strongly recommends that licensed professionals be used in the design and installation of lighting systems that include Elemental LED products. The specifications include important information that a designer and installer should carefully review and strictly follow. Qualified designers and certified and/or licensed installers, with access to the final installation environment, customer goals, and Elemental LED product specifications can make the requisite decisions appropriate for a successful finished lighting application.